

POLYMER ELECTROLYTE MEMBRANE AND METHOD OF PRODUCTION THEREOF

Patent number: WO0163683

Publication date: 2001-08-30

Inventor: TANIGUCHI TAKUMI (JP); NAKANO MITSURU (JP);
KAWASUMI MASAYA (JP); MORIMOTO YU (JP);
HASEGAWA NAOKI (JP)

Applicant: TOYOTA MOTOR CO LTD (JP); TANIGUCHI TAKUMI
(JP); NAKANO MITSURU (JP); KAWASUMI MASAYA
(JP); MORIMOTO YU (JP); HASEGAWA NAOKI (JP)

Classification:

- international: H01M8/10

- european: C08J5/22B4; H01M8/10E2

Application number: WO2001IB00231 20010221

Priority number(s): JP20000046541 20000223

Also published as:



WO0163683 (A3)

US2003087972 (A1)

JP2001236973 (A)

Cited documents:



WO9740924

WO9725369

WO9613872

JP9100386

XP002157864

Report a data error here

Abstract of WO0163683

A Polymer Electrolyte Membrane is formed by hot air drying of a membrane formed with an acidic main-polymer having proton conductivity and capability of forming an electrolyte membrane (S12), and then immersing it into a basic polymer solution to impregnate the membrane with the basic polymer (S14). The basic polymer is introduced in a large quantity into a site acting as a proton conduction pass of the main-polymer to take charge of the proton conduction. Since in the Polymer Electrolyte Membrane, a base polymer takes charge of proton conduction as compared with the case where proton takes charge of the proton conduction as a hydrate, the base polymer shows favorable proton conductivity even in a low humidity state at an elevated temperature exceeding boiling point of water.

